

BUS SHELTER PROTECTION

FROM GRAFFITI AND VANDALISM



EXTERIOR & INTERIOR STAINLESS STEEL · ADVERTISING PANELS · MAP PANELS · SEATING AREAS · SIDE & BACK GLASS PANELS · DIGITAL DISPLAYS



Protect Bus Shelters with 3M[™] Scotchgard[™] 1004 4-ply film

One installation of 3M[™] Scotchgard[™] Multi-Layer Protective Film will protect the glass and metal surfaces of your bus shelters from graffiti, scratches and other forms of vandalism, allowing you to peel away four graffiti defacements in seconds so you can:

- Maintain your good image
- Deter further vandalism
- Reduce replacement costs
- Provide a safe-feeling environment
- Save time refreshing surfaces

Interior & exterior surface protection where you need it most





EXTERIOR & INTERIOR STAINLESS STEEL · ADVERTISING PANELS · MAP PANELS · SEATING AREAS · SIDE & BACK GLASS PANELS · DIGITAL DISPLAYS

PROTECTION FROM ACID, SCRATCHES, PERMANENT MARKER, HARDWARE STAINS, GRAFFITI VANDALISM

Product Description

3M Scotchgard[™] Multi-layer Protective Film is an optically transparent, pressure-sensitive polyester film tapes designed to protect surfaces from intentional and unintentional damage caused by scratching, etching, abrasion and graffiti.

- Optically transparent view
- Clean removal leaves no adhesive residue

Four individual peel-away layers with a single installation

Why Bus Shelters?

Bus shelters are used daily and as such are subject to a high incidence of vandalism and graffiti. Protecting your bus shelters from such damage saves maintenance costs and enhances the overall customer experience.

Why 3M Scotchgard[™] Multi-layer Protective Film?

Competitive films only offer protection for a single incident. Only 3M Scotchgard[™] Multi-layer Protective Film provides 4 individual peel-away layers with a single installation.

Features

- Durable top-coat layer prevents light scratches caused by installation wiping, cleaning or abrasion.
- Optimized adhesive provides easy, clean removal from glass and most other surfaces.
- Optimized inter-layer adhesive provides firm, adequate adhesion yet fast and easy removal.
- High clarity construction provides glass-like appearance
- Blocks more than 98% of UV light that can degrade plastics and fabrics.
- May be used outdoors for short term use (typically <1 year) with minimal change in haze, clarity, light transmission and minimal adhesive residue left on most surfaces. Some exposure conditions (eg. direct sun facing, higher temperatures) may shorten performance.

A DAMAGED FILM LAYER CAN BE QUICKLY AND EASILY REMOVED, EXPOSING A FRESH PROTECTIVE SHEET



SIDE & BACK GLASS PANELS
DIGITAL DISPLAYS



EXTERIOR & INTERIOR STAINLESS STEEL · ADVERTISING PANELS · MAP PANELS · SEATING AREAS





FOR CLEAN REMOVAL ON SMOOTH SURFACES SUCH AS GLASS, MIRRORS AND POLISHED STAINLESS STEEL



Tested for Standards and Regulations

3M[™] Scotchgard[™] Multi-Layer Protective Film has been tested to the following standards and regulations:

- ANSI z26.1-1996 test #6
- Impact testing on tempered glass
- ASTM E-162
- Surface flammability of materials using a radiant heat energy source
- ASTM E-662
- Specific optical density of smoke generated by solid materials
- FMVSS/CMVSS 302
- Federal motor vehicle safety regulations flammability test
- Bombardier SMP 800-C
- Toxic gas generation
- ASTM D-1003
- Haze and luminous transmittance of transparent plastics
- ASTM E-313
- Yellowness and whiteness indices from instrumentally measured color coordinates
- ASTM D-4060-07
- Abrasion resistance of organic coatings by the taber abraser

EXTERIOR & INTERIOR STAINLESS STEEL · ADVERTISING PANELS · MAP PANELS · SEATING AREAS · SIDE & BACK GLASS PANELS · DIGITAL DISPLAYS

FOUR SEPARATE LAYERS OF OPTICALLY TRANSPARENT, PRESSURE-SENSITIVE POLYESTER FILM TAPE

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



npsgroup.com

INPS Group
3M-1004Film@inps.net
1.800.565.3509
+1.519.455.7647

